Wall-Mouted Speaker

ARVOX





Product Features:

* Two-way waterproof wall-mounted speaker with user-friendly design and easy installation;
* Equipped with full aluminum alloy mesh cover and aluminum alloy U-shaped bracket, rust-proof permanently;
* Adopts 6.5-inch 4-thread CD wire drawing process waterproof woofer and 25mm neodymium magnet dome silk membrane tweeter;
* Sturdy and thick new ABS plastic shell with anti-ultraviolet coating, preventing the shell from yellowing easily;
* The speaker features a fully sealed cabinet and passive diaphragm design, delivering fuller bass;
* The shell is additionally sprayed with oil for a smoother surface, available in black and white, suitable for various venues;
* The back cover is equipped with an input mode selection switch, enabling free switching between 8Ω, 70V, and 100V;
* The 70V and 100V terminals are equipped with built-in power selection switches, offering 5 adjustable power levels to be compatible with different venues;
* Waterproof design with an IP66 protection rating, suitable for all-weather environments;
* Comes standard with a U-shaped mounting bracket and fixed screw set, supporting angle adjustment;
* Suitable for indoor and outdoor applications, such as parks, swimming pools, shopping malls, cafes, meeting rooms and other background music venues;

Model NO.	R-940
70V Adjustable Power	40W, 20W, 10W, 5W, 2.5W
100V Adjustable Power	40W, 20W, 10W, 5W
8Ω Rated Power	60W
Frequency Response	60Hz-20KHz
Maximum Sound Pressure Level	102dB±3dB
Overall Dimensions	285×200×195mm (excluding bracket dimensions)
Installation Type	Adjustable mounting bracket
Decorative Materials	PP shell + aluminum alloy mesh cover
Speaker Units	6.5”×1 + 1”×1
Waterproof Rating	IP66
Weight	3.6kg