


MODEL NO.	R-H7080
Rated Power (8Ω)	80W
Maximum Power	200W
Input	8Ω
Sensitivity (1W/1M)	96dB ± 3dB
Frequency Response	80Hz - 18KHz
Radiation Angle	∠110°
Speaker Units	6.5 x 1, 1 x 1 (Coaxial)
Product Dimensions HxWxD	200 x 220 x 215 mm
Color	Black/White
Product Weight	3.8 KG
Protection Rating	IP65

MODEL NO.	R-H7080F
Rated Power (100V)	10W/20W/40W/80W
Rated Power (70V)	5W/10W/40W/80W
Rated Power (8Ω)	80W
Maximum Power	200W
Input	70V/100V/8Ω
Sensitivity (1W/1M)	96dB ± 3dB
Frequency Response	80Hz - 18KHz
Radiation Angle	∠110°
Speaker Units	6.5 x 1, 1 x 1 (Coaxial)
Product Dimensions HxWxD	200 x 220 x 215 mm
Color	Black/White
Product Weight	4.6 KG
Protection Rating	IP65







MODEL NO.	R-H8080
Rated Power (8Ω)	80W
Maximum Power	150W
Input	8Ω
Sensitivity (1W/1M)	96dB ± 3dB
Frequency Response	100Hz - 18KHz
Radiation Angle	/
Speaker Units	6.5 x 1, 1 x 1 (Coaxial)
Product Dimensions HxWxD	298x363x350mm
Color	Black/White
Product Weight	6.1 kg
Protection Rating	IP66

MODEL NO.	R-H8080F
Rated Power (100V)	10W/20W/40W/80W
Rated Power (70V)	5W/10W/40W/80W
Rated Power (8Ω)	80W
Maximum Power	150W
Input	70V/100V/8Ω
Sensitivity (1W/1M)	96dB ± 3dB
Frequency Response	80Hz - 18KHz
Radiation Angle	/
Speaker Units	6.5 x 1, 1 x 1 (Coaxial)
Product Dimensions HxWxD	298x363x350mm
Color	Black/White
Product Weight	6.7 KG
Protection Rating	IP67